



Features

- Rugged design stands up to field use
- Measures/Sources volts, mA, RTDs, thermocouples, frequency, and ohms
- 0.02% output and measurement accuracy
- Easy-to-read measure/source screen lets you view input and output simultaneously
- Perform fast linearity tests with auto step and auto ramp features
- Powers transmitters during the test using a loop supply with simultaneous mA measurement
- Measures and outputs 10 types of RTDs and 12 types of TC signals
- Rechargeable Ni-MH battery
- Adjustable brightness provides better visibility in poor light
- Store frequently-used test setups for later use
- Low battery indicator and auto shut-off
- Includes test leads, test clips, type K thermocouple wire probe, USB cable, power adapter, carrying case

Continued...

Specifications

Measure Function

Function	Range	Resolution	Accuracy
DC Voltage	50, 500mV, 30V (upper display), 50V (lower display)	0.001, 0.01, 1mV, 0.001V	50mV: $\pm(0.02\% +10)$ 500mV: $\pm(0.02\% +5)$ 30V (upper display): $\pm(0.02\% +2)$ 50V (lower display): $\pm(0.02\% +2)$
DC Current	20mA at 0 to 24mA	0.001mA	$\pm(0.02\% +2)$
Loop Current	20mA (loop) at 0 to 24mA		
Resistance	500, 5000 Ω	0.01, 0.1 Ω	$\pm(0.05\% +10)$
Frequency	100Hz, 1, 10, 100kHz	0.01, 0.1, 1Hz	$\pm(0.01\% +1)$

Thermocouples

Thermocouple	Range	Resolution	Accuracy
Type R	32 to 3212.6°F (0 to 1767°C)	1°F/°C	32 to 932°F (0 to 500°C): $\pm 3.24^\circ\text{F} (\pm 1.8^\circ\text{C})$
Type S			932 to 3212.6°F (500 to 1767°C): $\pm 2.7^\circ\text{F} (\pm 1.5^\circ\text{C})$
Type B	1112 to 3308°F (600 to 1820°C)	1°F/°C	1112 to 1472°F (600 to 800°C): $\pm 3.96^\circ\text{F} (\pm 2.2^\circ\text{C})$ 1472 to 1832°F (800 to 1000°C): $\pm 3.24^\circ\text{F} (\pm 1.8^\circ\text{C})$ 1832 to 3308°F (1000 to 1820°C): $\pm 2.52^\circ\text{F} (\pm 1.4^\circ\text{C})$
Type E	-58 to 1832°F (-50 to 1000°C)	0.1°F/°C	-58 to 32°F (-50 to 0°C): $\pm 1.62^\circ\text{F} (\pm 0.9^\circ\text{C})$ 32 to 1832°F (0 to 1000°C): $\pm 2.7^\circ\text{F} (\pm 1.5^\circ\text{C})$
Type K	-148 to 2501.6°F (-100 to 1372°C)	0.1°F/°C	-148 to 32°F (-100 to 0°C): $\pm 2.16^\circ\text{F} (\pm 1.2^\circ\text{C})$ 32 to 2501.6°F (0 to 1372°C): $\pm 1.44^\circ\text{F} (\pm 0.8^\circ\text{C})$
Type J	-76 to 2192°F (-60 to 1200°C)		-76 to 32°F (-60 to 0°C): $\pm 1.8^\circ\text{F} (\pm 1^\circ\text{C})$ 32 to 2192°F (0 to 1200°C): $\pm 1.26^\circ\text{F} (\pm 0.7^\circ\text{C})$
Type T	-148 to 752°F (-100 to 400°C)	0.1°F/°C	-148 to 32°F (-100 to 0°C): $\pm 1.8^\circ\text{F} (\pm 1^\circ\text{C})$ 32 to 752°F (0 to 400°C): $\pm 1.26^\circ\text{F} (\pm 0.7^\circ\text{C})$
Type N	-328 to 2372°F (-200 to 1300°C)		-328 to 32°F (-200 to 0°C): $\pm 2.7^\circ\text{F} (\pm 1.5^\circ\text{C})$ 32 to 2372°F (0 to 1300°C): $\pm 1.62^\circ\text{F} (\pm 0.9^\circ\text{C})$
Type L	-328 to 1652°F (-200 to 900°C)	0.1°F/°C	-328 to 32°F (-200 to 0°C): $\pm 1.53^\circ\text{F} (\pm 0.85^\circ\text{C})$ 32 to 1652°F (0 to 900°C): $\pm 1.26^\circ\text{F} (\pm 0.7^\circ\text{C})$
Type U	-328 to 752°F (-200 to 400°C)	0.1°F/°C	-328 to 32°F (-200 to 0°C): $\pm 1.98^\circ\text{F} (\pm 1.1^\circ\text{C})$ 32 to 752°F (0 to 400°C): $\pm 1.35^\circ\text{F} (\pm 0.75^\circ\text{C})$
Type XK	-328 to 1472°F (-200 to 800°C)		-328 to -148°F (-200 to -100°C): $\pm 0.9^\circ\text{F} (\pm 0.5^\circ\text{C})$ -148 to 1472°F (-100 to 800°C): $\pm 1.08^\circ\text{F} (\pm 0.6^\circ\text{C})$
Type BP	32 to 4532°F (0 to 2500°C)	0.1°F/°C	32 to 1472°F (0 to 800°C): $\pm 2.16^\circ\text{F} (\pm 1.2^\circ\text{C})$ 1472 to 4532°F (800 to 2500°C): $\pm 4.5^\circ\text{F} (\pm 2.5^\circ\text{C})$

TECHNICAL DATA

RTDs

RTD	Range	Resolution	Accuracy
Pt100 (2-wire/3-wire)	-328 to 1562°F (-200 to 850°C)	0.1°F/°C	$\pm 0.72^\circ\text{F} (\pm 0.4^\circ\text{C})$
Pt100 (4-wire)			$\pm 0.54^\circ\text{F} (\pm 0.3^\circ\text{C})$
Pt200 (2-wire/3-wire)	-328 to 1166°F (-200 to 630°C)	0.1°F/°C	-328 to 482°F (-200 to 250°C): $\pm 0.54^\circ\text{F} (\pm 0.3^\circ\text{C})$ 482 to 1166°F (250 to 630°C): $\pm 2.88^\circ\text{F} (\pm 1.6^\circ\text{C})$
Pt200 (4-wire)			-328 to 482°F (-200 to 250°C): $\pm 0.36^\circ\text{F} (\pm 0.2^\circ\text{C})$ 482 to 1166°F (250 to 630°C): $\pm 1.44^\circ\text{F} (\pm 0.8^\circ\text{C})$
Pt500 (2-wire/3-wire)	-328 to 932°F (-200 to 500°C)	0.1°F/°C	-328 to 932°F (-200 to 500°C): $\pm 1.08^\circ\text{F} (\pm 0.6^\circ\text{C})$ 932 to 1166°F (500 to 630°C): $\pm 1.62^\circ\text{F} (\pm 0.9^\circ\text{C})$
Pt500 (4-wire)			-328 to 932°F (-200 to 500°C): $\pm 0.72^\circ\text{F} (\pm 0.4^\circ\text{C})$ 932 to 1166°F (500 to 630°C): $\pm 0.72^\circ\text{F} (\pm 0.4^\circ\text{C})$
Pt1000 (2-wire/3-wire)	-328 to 1202°F (-200 to 650°C)	0.1°F/°C	$\pm 0.54^\circ\text{F} (\pm 0.3^\circ\text{C})$
Pt1000 (4-wire)			$\pm 0.27^\circ\text{F} (\pm 0.15^\circ\text{C})$
Cu10	-148 to 500°F (-100 to 260°C)	0.1°F/°C	$\pm 3.24^\circ\text{F} (\pm 1.8^\circ\text{C})$
Cu50 (2-wire/3-wire)			$\pm 1.44^\circ\text{F} (\pm 0.8^\circ\text{C})$
Cu50 (4-wire)	-58 to 302°F (-50 to 150°C)	0.1°F/°C	$\pm 0.9^\circ\text{F} (\pm 0.5^\circ\text{C})$
Cu100 (2-wire/3-wire)			$\pm 0.72^\circ\text{F} (\pm 0.4^\circ\text{C})$
Cu100 (4-wire)			$\pm 0.45^\circ\text{F} (\pm 0.25^\circ\text{C})$
Pt100-392 (2-wire/3-wire)	-328 to 1166°F (-200 to 630°C)	0.1°F/°C	$\pm 0.9^\circ\text{F} (\pm 0.5^\circ\text{C})$
Pt100-392 (4-wire)			$\pm 0.54^\circ\text{F} (\pm 0.3^\circ\text{C})$
Pt100-JIS (2-wire/3-wire)	-328 to 1166°F (-200 to 630°C)	0.1°F/°C	$\pm 0.9^\circ\text{F} (\pm 0.5^\circ\text{C})$
Pt100-JIS (4-wire)			$\pm 0.54^\circ\text{F} (\pm 0.3^\circ\text{C})$
Ni120 (2-wire/3-wire)	-112 to 500°F (-80 to 260°C)	0.1°F/°C	$\pm 0.54^\circ\text{F} (\pm 0.3^\circ\text{C})$
Ni120 (4-wire)			$\pm 0.36^\circ\text{F} (\pm 0.2^\circ\text{C})$

Source Function

Function	Range	Resolution	Accuracy
DC Voltage	100mV, 1, 10V	0.001, 0.01mV, 0.0001V	$\pm(0.02\% +10)$
DC Current	20mA at 0 to 24mA 20mA (SIM) at 0 to 24mA	0.001mA	$\pm(0.02\% +2)$
Resistance	400, 4000 Ω , 40k Ω	0.01, 0.1, 1 Ω	$\pm(0.02\% +8)$ $\pm(0.05\% +10)$ $\pm(0.1\% +40)$
Frequency	200, 2000Hz, 20, 100kHz	0.01, 0.1, 1, 10Hz	$\pm(0.01\% +1) (\pm 3 \text{ dgt.})$ 100kHz: $\pm 5 \text{ dgt.}$
Pulse	100Hz, 1, 10kHz	1 cyc	$\pm 2 \text{ dgt.}$
Switch Quantity	100Hz, 1, 10, 100kHz	0.01, 0.1, 1, 10Hz	

Continued...

Thermocouples

Thermocouple	Range	Resolution	Accuracy
Type R	32 to 3212.6°F (0 to 1767°C)	1°F/°C	32 to 212°F (0 to 100°C): ±2.7°F (±1.5°C)
Type S			212 to 3212.6°F (100 to 1767°C): ±2.16°F (±1.2°C)
Type B	1112 to 3308°F (600 to 1820°C)		1112 to 1472°F (600 to 800°C): ±2.7°F (±1.5°C) 1472 to 3308°F (800 to 1820°C): ±1.98°F (±1.1°C)
Type E	-328 to 1832°F (-200 to 1000°C)	0.1°F/°C	-328 to -148°F (-200 to -100°C): ±1.08°F (±0.6°C) -148 to 1112°F (-100 to 600°C): ±0.9°F (±0.5°C) 1112 to 1832°F (600 to 1000°C): ±0.72°F (±0.4°C)
Type K	-328 to 2501.6°F (-200 to 1372°C)		-328 to -148°F (-200 to -100°C): ±1.08°F (±0.6°C) -148 to 752°F (-100 to 400°C): ±0.9°F (±0.5°C) 752 to 2192°F (400 to 1200°C): ±1.26°F (±0.7°C) 2192 to 2501.6°F (1200 to 1372°C): ±1.62°F (±0.9°C)
Type J	-328 to 2192°F (-200 to 1200°C)		-200 to -148°F (-200 to -100°C): ±1.08°F (±0.6°C) -148 to 1472°F (-100 to 800°C): ±0.9°F (±0.5°C) 1472 to 2192°F (800 to 1200°C): ±1.26°F (±0.7°C)
Type T	-418 to 752°F (-250 to 400°C)		±1.08°F (±0.6°C)
Type N	-328 to 2372°F (-200 to 1300°C)		-328 to -148°F (-200 to -100°C): ±1.8°F (±1°C) -148 to 1652°F (-100 to 900°C): ±1.26°F (±0.7°C) 1652 to 2372°F (900 to 1300°C): ±1.44°F (±0.8°C)
Type L	-328 to 1652°F (-200 to 900°C)		-328 to 32°F (-200 to 0°C): ±1.53°F (±0.85°C) 32 to 1652°F (0 to 900°C): ±1.26°F (±0.7°C)
Type U	-328 to 752°F (-200 to 400°C)		-328 to 32°F (-200 to 0°C): ±1.98°F (±1.1°C) 32 to 752°F (0 to 400°C): ±1.35°F (±0.75°C)
Type XK	-328 to 1472°F (-200 to 800°C)		-328 to -148°F (-200 to -100°C): ±0.9°F (±0.5°C) -148 to 1472°F (-100 to 800°C): ±1.08°F (±0.6°C)
Type BP	32 to 4532°F (0 to 2500°C)	32 to 1472°F (0 to 800°C): ±2.16°F (±1.2°C) 1472 to 4532°F (800 to 2500°C): ±4.5°F (±2.5°C)	

RTDs

RTD	Range	Resolution	Accuracy	
Pt100-385	-328 to 1472°F (-200 to 800°C)	0.1°F/°C	±0.6°F (±0.33°C)	
Pt100-392	-328 to 1166°F (-200 to 630°C)		±0.54°F (±0.3°C)	
Pt200-385			-328 to 482°F (-200 to 250°C): ±0.36°F (±0.2°C) 482 to 1166°F (250 to 630°C): ±1.44°F (±0.8°C)	
Pt100-JIS			±0.54°F (±0.3°C)	
Pt500-385			-328 to 932°F (-200 to 500°C): ±0.54°F (±0.3°C) 932 to 1166°F (500 to 630°C): ±0.72°F (±0.4°C)	
Pt1000-385			±0.36°F (±0.2°C)	
Cu10			-148 to 500°F (-100 to 260°C)	±3.24°F (±1.8°C)
Cu50			-58 to 302°F (-50 to 150°C)	±0.9°F (±0.5°C)
Cu100			±0.45°F (±0.25°C)	
Ni120			-112 to 500°F (-80 to 260°C)	±0.36°F (±0.2°C)

Continued...

Function Specifications

Ramp Functions:	Source functions: Voltage, Current, Resistance, Frequency, Temperature Ramps: Slow ramp, fast ramp, 25% step-ramp
Loop Power Function:	Voltage: 24V Accuracy: 10% Maximum current: 22mA, short circuit protected
Step Functions:	Source functions: Voltage, Current, Resistance, Frequency, Temperature Steps: 25% of range, 100% of range

General Specifications

Display:	20,000 count TFT color LCD display
Kick Stand:	Yes
Power Supply:	1.2V x 6 AA rechargeable batteries
Auto shut-off:	Yes
Low Battery Indicator:	Yes
Replaceable Test Leads:	Yes
Product Certifications:	CE, RoHS
Operating Temperature:	14 to 131°F (-10 to 55°C)
Operating Humidity Range:	≤95%
Storage Temperature:	-4 to 158°F (-20 to 70°C)
Max Operating Altitude:	6561' (2000m)
Dimensions:	7.7 x 3.7 x 2.3" (195 x 95 x 58mm)
Weight:	22.92oz (650g)

Model	Description
R5850	Multifunction Process Calibrator
TP-01	Type K Beaded Wire Probe
R1000	Safety Test Lead Set
R1020	Fused Test Lead Set
R2920	Type K Surface Probe
R2930	Type K Right Angle Surface Probe
R2940	Type K Air/Gas Probe
R2950	Type K Immersion Probe
R2960	Type K Needle Tip Probe
R8888	Medium Hard Carrying Case
R1050-KIT2	Deluxe Safety Test Lead Kit
R5850-NIST	Multifunction Process Calibrator & NIST